

38th Street 3800 N OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION 21 TOWNSHIP 16 DATE: -9-24-01- 8-25-06 PARTY CHIEF: Wilcoxen CREW: -TYPE OF MARKER: Harrison Ave 9 - 9 - 96METHOD OF ESTABLISHMENT: County: IN. S.P.C. E ZONE NAD '83 + 16032102 NAME: N: 508157.0690(m) 3 E: 53756.2310(m) 20 246 + 15. 1. Edge of Pavement 3. 00 193.40 101.07' % Section Line W. 38th Street ■ Mile marker 117/8 post

Original post set 1820 by Wm. B. Laughlin with witnesses: 10" hornbeam N 29 E 25 links, 12' buckeye S 43 W 14 links per Marion County Atlas pg. 7. Survey by Wm. P. Smith on 3-11-1870 indicates no stone or witness per Wayne Township Legal Survey Book pg. 64. Universaw 7-14-55 called a boat spike. G.W.S. 4-5-63 called boat spike, G.W.S. 6-29-64 called a railroad spike. Miller 12-3-75 called a brass plug. McCarthy 8-15-86 called a brass plug. Wilcoxen 9-9-96 called a brass plug. Excavated by Wilcoxen 8-16-01 and Harrison set. Harrison set in position as the corner using G.P.S. coordinates. No other points were found. As a result of interstate construction. Re-tied 9-24-01 by Wilcoxen. 16032102

REF.	DISTANCE	DESCRIPTION
1.	17.00'	Due N to edge of pavement
2.	101.07*	Cut 'x' NW bolt of aluminum pole base
3.	193.40	Cut 'x' SE-bolt of aluminum pole base
		E DE O